

1. Unique identification code of the product-type:

Precast Concrete Bricks

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Solid Facing Bricks Cameron Mixture

3. Intended use or uses of the construction product, in accordance with the applicable designated technical specification, as foreseen by the manufacturer:

Domestic and Commercial use in Walls, Columns and Partitions

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Marshalls Bricks and Masonry, Blencowe Works, Nr. Newbiggin, Stainton, Penrith, CA11 0DE.

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 4

7. In case of the declaration of performance concerning a construction product covered by a designated standard:

BS EN 771-3:2011+A1: 2015

8. In case of the declaration of performance concerning a construction product for which a UK Assessment Document has been issued:

Not applicable

9. Declared performance

| Essential Characteristics | Performance Value | | Relevant Clause within EN 771-3:2011+A1:2015 |
|--|--|------------------------------|---|
| Dimensions and Dimensional Tolerances | Length 215mm Width 100mm Height 65mm Tolerance D1 | | Clauses 5.2.1 & 5.2.2 BSEN 771-3:2011+A1:2015 |
| Configuration (1) | Shape and Features | NPD | BSEN 771-3:2011+A1:2015 |
| | Group according to EN 1996-1-1 (EC6) | Group 1 | |
| Compressive Strength | Mean Compressive Strength | >22.5N/mm2 | Clause 5.5.1 BSEN 771-3:2011+A1:2015 |
| | Direction of load | Perpendicular to bed faces | |
| | Unit Category | Category 11 | |
| Dimensional Stability (1) | <0.6mm/m | | Clause 5.9 BSEN 771-3:2011+A1:2015 |
| Bond Strength | Shear bond strength | 0.15N/mm2 (tabulated values) | Clause 5.12 & 5.13 BSEN 771-3:2011+A1:2015 |
| | Flexural bond strength | NPD | |
| Reaction to Fire (2) | Class A1 | | Clause 5.11 Commission Decision 2000/605/EC |
| Water Absorption (3) | <20g/m2/s 0.5 | | Clause 5.11 BSEN 771-3:2011+A1:2015 |
| Water Vapour Permeability (4) | 5/15μ (Tabulated value) | | Clause 5.10 BSEN 771-3:2011+A1:2015 |
| Direct Airborne Sound Insulation (5) (in end conditions)/(Density and configuration) | Gross density | 2200Kg/m3 | Clause 5.4 BSEN 771-3:2011+A1:2015 |
| | Configuration | Group 1 | |
| Thermal Resistance | 1.37W/mk (@90%) | | Clause 5.6 BSEN 771-3:2011+A1:2015 |
| | 2200Kg/M3 | | |
| | Group 1 | | |
| Durability against Freeze Thaw | Frost resistant moderate exposure | | Clause 5.7 BSEN 771-3:2011+A1:2015 |
| Dangerous Substances | NPD | | |

- (1) For units intended to be used in elements subject to structural requirements
- (2) For units intended to be used in elements subject to fire requirements
- (3) For units intended to be used in damp proof courses or in external elements with exposed face
- (4) For units intended to be used in external elements
- (5) For units to be used in elements subject to acoustic requirements

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

Not applicable

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, As it has effect in the United Kingdom under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Simon Bourne

Chief Commercial Officer

Date: 24th March 2025

Place of Issue: Elland, Halifax, UK