### GB Declaration of Performance: CBP - 191



Marshalls Mono Ltd, Landscape House, Lowfields Business Park, Elland, West Yorkshire HX5 9HT

Registered in England: 509579

1. Unique identification code of the product-type:

## **Precast Concrete Block Paving**

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

## Modal X Textured

# Oatmeal Granite, Charcoal Granite, Light Granite, Silver Grey Granite, Light Cream Granite, Pink Granite, Mid Grey Granite

3. Intended use or uses of the construction product, in accordance with the applicable designated technical specification, as foreseen by the manufacturer:

Domestic/Commercial use; for road finishes and covering external pedestrian and vehicular circulation areas. Internal flooring when installed in enclosed e.g. public transport premises (see Marshalls Product Selector brochure for guidance on applications)

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

### Marshalls, Meadow Lane, St. Ives, Cambridgeshire PE27 4LG

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

#### Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

## System 4

7. In case of the declaration of performance concerning a construction product covered by a designated standard:

## BS EN 1338:2003

8. In case of the declaration of performance concerning a construction product for which a UK Assessment Document has been issued:

#### Not applicable

#### **GB** Declaration of Performance: **CBP** – **191**



Marshalls Mono Ltd, Landscape House, Lowfields Business Park, Elland, West Yorkshire HX5 9HT

Registered in England: 509579

#### 9. Declared performance

Essential Characteristics	Performance	Relevant Clause of BS EN 1338:2003
Reaction to Fire	Class A1 when used for internal flooring	5.3.6.1
External Fire performance	Deemed to satisfy when used for roofing	5.3.6.2
Emission of asbestos	No Content	4.2
Tensile Splitting Strength	≥ 3.6 MPa	5.3.3 of Annex F
Slip / Skid resistance ( only when tested )	≥ 45	5.3.5 of Annex I
Durability	Satisfactory	5.3.2, 5.3.3.3 & 5.3.5.3

*Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:* 

#### Not applicable

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, As it has effect in the United Kingdom" under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Linn Denn.

Simon Bourne Chief Commercial Officer Date: 4<sup>th</sup> June 2024

Place of Issue: Elland, Halifax, UK

Version History: Updated due to change in Director's responsibilities.

# **GB** Declaration of Performance: CBP – 191





Registered in England: 509579