

*1. Unique identification code of the product-type:*

**Precast Concrete Block Paving**

*2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):*

**Falkirk Round Top Edgings**

*3. Intended use or uses of the construction product, in accordance with the applicable designated technical specification, as foreseen by the manufacturer:*

**Domestic/Commercial use; for road finishes and covering external pedestrian and vehicular circulation areas. Internal flooring when installed in enclosed e.g. public transport premises (see Marshall's Product Selector brochure for guidance on applications)**

*4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):*

**Marshall's, Falkirk Works, Dollar Industrial Estate, Falkirk, Stirlingshire, FK2 7YS**

*5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):*

**Not applicable**

*6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:*

**System 4**

*7. In case of the declaration of performance concerning a construction product covered by a designated standard:*

**BS EN 1338:2003**

*8. In case of the declaration of performance concerning a construction product for which a UK Assessment Document has been issued:*

**Not applicable**

*9. Declared performance*

| Essential Characteristics                   | Performance                              | Relevant Clause of BS EN 1338:2003 |
|---|--|------------------------------------|
| Reaction to Fire                            | Class A1 when used for internal flooring | 5.3.6.1                            |
| External Fire performance                   | Deemed to satisfy when used for roofing  | 5.3.6.2                            |
| Emission of asbestos                        | No Content                               | 4.2                                |
| Tensile Splitting Strength                  | ≥ 3.6 MPa                                | 5.3.3 of Annex F                   |
| Slip / Skid resistance ( only when tested ) | ≥ 45                                     | 5.3.5 of Annex I                   |
| Durability                                  | Satisfactory                             | 5.3.2, 5.3.3.3 & 5.3.5.3           |

*Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:*

**Not applicable**

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, As it has effect in the United Kingdom” under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Simon Bourne

Chief Commercial Officer

Date: 23<sup>rd</sup> June 2025

Place of Issue: Elland, Halifax, UK