Marshalls Mono Ltd, Landscape House, Lowfields Business Park, Elland, West Yorkshire HX5 9HT

Registered in England: 509579

1. Unique identification code of the product-type:

Modular Tiles of Natural Stone

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Cantarini

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Modular tiles of natural Stone for flooring and stairs, Internal use (see Marshalls brochure for guidance on applications)

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Marshalls, Landscape House, Premier Way, Lowfields Business Park, Elland, West Yorkshire, HX5 9HT

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 4

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

BS EN 12057:2004

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not applicable





Marshalls Mono Ltd, Landscape House, Lowfields Business Park, Elland, West Yorkshire HX5 9HT *9. Declared performance*

Registered in England: 509579

Essential Characteristics	Performance		Relevant Clause of BS EN 12057:2004
Petrographic	Denomination: Marble from Potugal, mainly snow white, mainly coarse grained marble, well to very well compacted, hard and robust		4.2.2
Reaction to Fire	Class A1 Without testing (see decision 96/603/EC, as amended		4.2.7
Flexural Strength	LEV 10.7MPa		4.2.4
Expressed as; Lowest Expected	Mean 16.3MPa		4.2.4 EN12372
Value (LEV) Mean Value and SD	SD 2.1		EN12372
Slip Resistance	Wet	Dry	4.2.14
(mean value)	2	43	EN 14231
Tactility/Visibility	See description on Brochure/data		4.2.15
	sheet		(visual)
Thermal Conductivity	From: 2700	To:2700	4.2.9
(Apparent density kg/m3)			EN 1936

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

Not applicable

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Rory Kendrick

International Stone Sourcing Director

Thalk

Date: 2nd August 2018

Version History: Version 3, August 2018 updated to amend to new DoP structure