

Tile and Stone Interiors

CONSTRUCTION PRODUCTS REGULATIONS DECLARATION OF PERFORMANCE

Relevant Harmonised Standard BSEN 12057:2004

Products Natural Stone Product

Denomination Indian Limestone from Mehta, Delhi, India

Uses Slabs of Natural Stone for flooring and stairs, internal use (see Marshalls Tile and Stone Interiors Natural Stone and Mosaics for guidance on applications)

Marshalls Tile and Stone Interiors Landscape House Premier Way Lowfields Business Park Elland, West Yorkshire, HX5 9HT United Kingdom

Year of first affixing CE Mark

16

KNIGHTSMILL Grey to grey/green, fine grained Limestone, hard to very hard		
Declared Performance		
Essential Characteristics	Performance Value	Relevant Clause EN 12057:2004
Reaction to Fire	Class A1 Without testing (see Decision 96/603/EC, as amended	42.7
Flexural strength Expressed as; Lowest Expected Value (LEV) Mean value and SD	LEV 19.79MPa Mean 22.6MPa SD 1.4	4.2.4 EN 12372
Slip Resistance (Wet Method)	16 (mean value)	4.2.14 EN 14231
Slip Resistance (Dry Method)	35 (mean value)	4.2.14 EN 14231
Tactility/Visibility	See description on Brochure/data sheet	4.2.15 (Visual)
Thermal Conductivity (Apparent density kg/m ³)	2708kg/m ³	4.2.9 EN 1936

Products are offered in line with the requirements of Attestation Level 4 as designated under the Construction Products Regulations (2011) Annex V. Type testing, routine testing and Factory Production Control documents have been developed and issued for this series of products.

I Hereby declare that the products named above are in conformity with the essential requirements of the Construction Products Regulations and the ZA Annex within the following Standard when installed in accordance with Marshalls Tile and Stone Interiors Natural Stone and Mosaicsinstallation guidelines.

EN 12057:2004

Declaration of Performance

Signed:

51. hik

Full name: Rory Kendrick

Position: International Stone Sourcing Director

Date: 31st August 2017