



## CONSTRUCTION PRODUCTS REGULATIONS DECLARATION OF PERFORMANCE

Relevant Harmonised Standard <b>BSEN 12057:2004</b>		
<b>Products</b> Natural Stone Products, 15-18mm Quartzite tiles		
<b>Denomination</b> Pale greenish grey with occasional feint orange/brown bands, mainly medium grained, robust and hard Quartzite, China		
<b>Uses</b> Modular tiles for flooring and walls for internal use (see Marshalls Tile and Stone Interiors Natural Stone and Mosaics for guidance on applications)		
<b>Marshalls plc</b> <b>Tile and Stone Interiors</b> <b>Landscape House,</b> <b>Premier Way,</b> <b>Lowfields Business Park,</b> <b>Halifax, HX5 9HT</b> <b>West Yorkshire</b>		Year of first affixing CE Mark  13
Noce		
Declared Performance		
Essential Characteristics	Performance Value	Relevant Clause EN 12057:2004
<b>Reaction to Fire</b>	<b>Class A1</b> Without testing (see Decision 96/603/EC, as amended)	4.2.7
<b>Release of Dangerous Substances</b>	None; (see Decision 76/69/EC as amended)	ZB.1
<b>Water Vapour Permeability</b>	<b>NPD</b>	4.2.12
<b>Flexural strength</b> Expressed as; Lowest Expected Value (LEV) Mean value and SD	<b>LEV 10.45 MPa</b>	4.2.4 EN 12372
	<b>Mean 15.04 MPa</b>	
	<b>SD 3.41</b>	
<b>Slip Resistance</b> (Wet Method)	<b>63</b>	4.2.14 EN 14231
<b>Slip Resistance</b> (Dry Method)	<b>83</b>	4.2.14 EN 14231
<b>Tactility/Visibility</b>	See description on Brochure/data sheet	4.2.15 (Visual)
<b>Direct Airborne Sound Insulation</b>	<b>NPD</b>	4.2.9 EN1936
<b>Thermal Conductivity</b> (Apparent density kg/m <sup>3</sup> )	<b>From 2630 – 2700 kg/m<sup>3</sup></b>	4.2.9 EN 1936

**Products are offered in line with the requirements of Attestation Level 4 as designated under the Construction Products Regulations (2011) Annex V. Type testing, routine testing and Factory Production Control documents have been developed and issued for this series of products.**

**I Hereby declare that the products named above are in conformity with the essential requirements of the Construction Products Regulations and the ZA and ZB Annexes within the following Standard when installed in accordance with Marshalls Tile and Stone Interiors Natural Stone and Mosaics installation guidelines.**

**EN 12057:2004**

### Declaration of Performance

Signed:



Full name: Rory Kendrick

Position: International Trading Director

Date: 15<sup>th</sup> May 2014

Document Amended: Address

Date: 1<sup>st</sup> February 2016

Document Amended: Referencing  
brochure title

Date: 7<sup>th</sup> July 2016