

CONSTRUCTION PRODUCTS REGULATIONS DECLARATION OF PERFORMANCE

Relevant Harmonised Standard

BSEN 1339:2003

Products Concrete Paving Flags: Standard Pimple Paving, Special Pressed Paving (Commercial), Pastel, Pastel Domestic Paving, Pendle, Richmond, Ferndale, Standard 25-38mm Paving, Tegula/Drivesett units>295mm/4:1 ratio L-W

Denomination Precast Concrete

Uses Commercial/Domestic use; for road finishes and covering external pedestrian and vehicular circulation areas. Internal flooring when installed in enclosed e.g. public transport premises (see Marshalls Product Selector brochure for guidance on applications)

Eaglescliffe Works, Durham Lane, Stockton on Tees, Cleveland, TS16 0PS

Declared Performance		
Essential Requirement	Performance Value	Relevant Clause within EN 1339:2003
Reaction to Fire	Class A1 when used for internal flooring	5.3.7.1
External Fire performance	Deemed to satisfy when used for roofing	5.3.7.2
Emission of asbestos	No Content	4.2
Bending Strength (MPa) & Breaking Load (kN)	>3.5MPa Class 1 >3kN >4.0MPa Class 2 >7kN >5.0MPa Class 3 >14kN	5.3.3 of Annex F
Abrasion Resistance (only classes 3 and 4)	<23mm	5.3.4 of Annex G
Slip / Skid resistance (only when tested)	>45	5.3.5 of Annex I
Durability	Satisfactory	5.3.3.4 & 5.3.5.3
	Satisfactory requirements of Attestation Level 4 as	

Products are offered in line with the requirements of Attestation Level 4 as designated under the Construction Products Regulations (2011) Annex V. Type testing, routine testing and Factory Production Control documents have been developed and issued for this series of products.

I Hereby declare that the products named above are in conformity with the essential requirements of the Construction Products Regulations and the following Standard when installed in accordance with Marshalls' installation guidelines.

EN 1339:2003

Full name: Tom Poole

Position: Managing Director Group Operations Date: 4th April 2014