#### **EU Declaration of Performance ME-141**



Marshalls Mono Ltd, Landscape House, Lowfields Business Park, Elland, West Yorkshire HX5 9HT

Registered in England: 509579

1. Unique identification code of the product-type:

#### **Slabs of Natural Stone**

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

#### **Brackendale Sawn Indian Sandstone Paving**

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

# Domestic/Commercial Paving for external uses (see Marshalls brochure for guidance on applications)

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

## Marshalls, Landscape House, Premier Way, Lowfields Business Park, Elland, West Yorkshire, HX5 9HT

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

#### Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

#### System 4

7. In case of the declaration of conformity concerning a construction product covered by a harmonised standard:

#### BS EN 1341:2012

8. In case of the declaration of performance concerning a construction product for which a European Technical Speciation has been issued:

#### Not applicable

March 2021 Page 1

#### **EU Declaration of Performance ME-141**



Marshalls Mono Ltd, Landscape House, Lowfields Business Park, Elland, West Yorkshire HX5 9HT

Registered in England: 509579

### 9. Declared performance

Essential Characteristics	Performance		Relevant Clause of BS EN 1341:2012	
Petrographic	Denomination: Light pinkish brown, fine grained Sandstone from Golpur, Rajasthan, India.		4.1.1	
Release of dangerous substances	NPD		4.11	
Flexural Strength Lowest expected Value	22.2MPa		4.4	
Slip Resistance (wet value)	Flamed	67	4.6.1	
	Flamed/Waterjet	71		
	Bush Hammered	66		
	Shot Blast	83		
Skid Resistance	NPD		4.6.2	
	(mean value)			
Freeze/thaw resistance				
(general)	28.6/26.8MPa		4.3.1	
Before and after 56 cycles				
Freeze/thaw resistance	NPD		4.3.2	
(De-Icing salts)			4.3.2	
Polishing In Use	NPD		4.6.3	

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

## Not applicable

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

Signed for and on behalf of the manufacturer by:

Simon Bourne Date: 25<sup>th</sup> March 2021

Group Operation Director Place of Issue: Elland, Halifax, UK

All EU Declarations from January 2021 will show Version 1 so as to be complimentary with our GB Declaration of Performance.

Sandburgs A and B report 69016 March 21

Please refer to the data sheet for the design of materials for construction

March 2021 Page 2