

1. Unique identification code of the product-type:

Slabs of Natural Stone

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Umbriel Dark Grey Granite Paving

3. Intended use or uses of the construction product, in accordance with the applicable designated technical specification, as foreseen by the manufacturer:

Domestic/Commercial Paving for external uses (see Marshall's brochure for guidance on applications)

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Marshall's, Landscape House, Premier Way, Lowfields Business Park, Elland, West Yorkshire, HX5 9HT

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 4

7. In case of the declaration of performance concerning a construction product covered by a designated standard:

BS EN 1341:2012

8. In case of the declaration of performance concerning a construction product for which a UK Technical Assessment has been issued:

Not applicable

9. Declared performance

Essential Characteristics	Performance			Relevant Clause of BS EN 1341:2012
Petrographic	Denomination: White to off white to pale grey with occasional black and shining spots, mainly coarse grained strong Granite from Portugal			4.1.1
Release of dangerous substances	NPD			4.11
Flexural Strength Lowest expected Value	15.8 MPa			4.4
Slip Resistance		Wet	Dry	4.6.1
	Sawn (Honed)	66	69	
	Blasted	78	91	
	Flamed	69	88	
Skid Resistance (Mean value)		Wet	Dry	4.6.2
	Sawn (Honed)	70	78	
	Blasted	76	90	
	Flamed	75	84	
Freeze/thaw resistance (general) Before and after 56 cycles	18.1/17.0MPa			4.3.1
Freeze/thaw resistance (De-Icing salts)	NPD			4.3.2
Polishing In Use	NPD			4.6.3

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

Not applicable

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



Simon Bourne

Date: 14th July 2026

Chief Executive Officer

Place of Issue: Elland, Halifax, UK

Sandburg A Report August 2025 ref 79124S B report CLTT 5095 July 2025