GB Declaration of Performance: ME-19



Marshalls Mono Ltd, Landscape House, Lowfields Business Park, Elland, West Yorkshire HX5 9HT

Registered in England: 509579

1. Unique identification code of the product-type:

Slabs of Natural Stone

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Standard Indian Sandstone Brown Multi Paving

3. Intended use or uses of the construction product, in accordance with the applicable designated technical specification, as foreseen by the manufacturer:

Domestic/Commercial Paving for external uses (see Marshalls brochure for guidance on applications)

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Marshalls, Landscape House, Premier Way, Lowfields Business Park, Elland, West Yorkshire, HX5 9HT

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 4

7. In case of the declaration of conformity concerning a construction product covered by a designated standard:

BS EN 1341:2012

8. In case of the declaration of conformity concerning a construction product for which a UK Assessment Document has been issued:

Not applicable

GB Declaration of Performance: ME-19



Marshalls Mono Ltd, Landscape House, Lowfields Business Park, Elland, West Yorkshire HX5 9HT

Registered in England: 509579

9. Declared performance

| Essential Characteristics | Performance | | Relevant Clause of BS EN 1341:2012 |
|---|---|----|---------------------------------------|
| Petrographic | Denomination: Kota Brown. Light reddish brown, generally fine grained SANDSTONE. India. | | 4.1.1 |
| Release of dangerous substances | NPD | | 4.11 |
| Flexural Strength Lowest expected Value | 28.84MPa | | 4.4 |
| | Flamed | 70 | 4.6.1 |
| Slip Resistance | Flamed & Waterjet | 79 | |
| (wet value) | Bush hammed/brushed | 69 | |
| | Shot blast | 79 | |
| Skid Resistance | NPD | | 4.6.2 |
| | Riven or textured surface | | |
| Freeze/thaw resistance (general) Before and after 56 cycles | 34.6/30.1MPa | | 4.3.1 |
| Freeze/thaw resistance (De-Icing salts) | NPD | | 4.3.2 |
| Polishing In Use | NPD | | 4.6.3 |

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

Not applicable

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, As it has effect in the United Kingdom under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Linn Down .

Simon Bourne Chief Commercial Officer Test Group 1 Sandburg A March 2021, Sandburg B March 2021, CLTT 4519 2023 Date: 24th April 2025

Place of Issue: Elland, Halifax,