

*1. Unique identification code of the product-type:*

**Slabs of Natural Stone**

*2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):*

**Towngate Buff Multi Paving**

*3. Intended use or uses of the construction product, in accordance with the applicable designated technical specification, as foreseen by the manufacturer:*

**Domestic/Commercial Paving for external uses (see Marshall's brochure for guidance on applications)**

*4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):*

**Marshall's, Landscape House, Premier Way, Lowfields Business Park, Elland, West Yorkshire, HX5 9HT**

*5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):*

**Not applicable**

*6. System or systems of assessment and verification of constancy of conformity of the construction product as set out in Annex V:*

**System 4**

*7. In case of the declaration of conformity concerning a construction product covered by a designated standard:*

**BS EN 1341:2012**

*8. In case of the declaration of conformity concerning a construction product for which a UK Technical Assessment has been issued:*

**Not applicable**

## UK Declaration of Performance: ME-297



Marshall's Mono Ltd, Landscape House, Lowfields Business Park, Elland, West Yorkshire HX5 9HT

Registered in England: 509579

### 9. Declared performance

Essential Characteristics	Performance	Relevant Clause of BS EN 1341:2012
Petrographic	Light reddish buff, generally fine grained SANDSTONE	4.1.1
Release of dangerous substances	NPD	4.11
Flexural Strength Lowest expected Value	29.49MPa	4.4
Slip Resistance (wet value)	Flamed	67
	Flamed & Waterjet	71
	Bush hammered/brushed	66
	Shot blast	83
Skid Resistance	NPD Riven or textured surface	4.6.2
Freeze/thaw resistance (general) Before and after 56 cycles	28.6/26.8MPa	4.3.1
Freeze/thaw resistance (De-Icing salts)	NPD	4.3.2
Polishing In Use	NPD	4.6.3

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

### Not applicable

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, As it has effect in the United Kingdom under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Simon Bourne

Chief Commercial Officer

Date: 24<sup>th</sup> April 2025

Place of Issue: Elland, Halifax,

Test Group 3 Sandburg A March 2021, Sandburg B March 2021, CLTT 4529 2023