Marshalls Mono Ltd, Landscape House, Lowfields Business Park, Elland, West Yorkshire HX5 9HT

Registered in England: 509579

1. Unique identification code of the product-type:

Setts of Natural Stone

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Carina Granite Setts

3. Intended use or uses of the construction product, in accordance with the applicable designated technical specification, as foreseen by the manufacturer:

Domestic/Commercial Paving Setts for external uses (see Marshalls brochure for guidance on applications)

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Marshalls, Landscape House, Premier Way, Lowfields Business Park, Elland, West Yorkshire HX5 9HT

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 4

7. In case of the declaration of performance concerning a construction product covered by a designated standard:

BS EN 1342:2012

8. In case of the declaration of performance concerning a construction product for which a UK Assessment Document has been issued:

Not applicable



Marshalls Mono Ltd, Landscape House, Lowfields Business Park, Elland, West Yorkshire HX5 9HT

9. Declared performance

| Essential Characteristics | Performance | | Relevant Clause of BS EN 1342:2012 |
|---|--|----------------|------------------------------------|
| Petrographic | Denomination: Light to medium grey, fine to medium grained METAGRANITE. The stone consisted of mainly interlocking crystals. Dark brown flaky minerals were well evenly distributed and exhibited a faint foliated texture. The stone was well compacted, hard and strong. | | 4.1.1 |
| Release of dangerous substances | NPD | | 4.11 |
| Compressive Strength Lowest expected Value | 136 MPa | | 4.4 |
| Slip Resistance (wet value) | Polished Flamed Shot blasted | 12 65 71 | 4.6.1 |
| Skid Resistance | NPD (mean value) | | 4.6.2 |
| Freeze/thaw resistance (general) Before and after 56 cycles | 24.7/25.8 MPa | | 4.3.1 |
| Freeze/thaw resistance (De-Icing salts) | NPD | | 4.3.2 |
| Polishing In Use | NPD | | 4.6.3 |

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

Not applicable

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, As it has effect in the United Kingdom" under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Simon Bourne Date: 1st December 2021

Group Operation Director Place of Issue: Elland, Halifax, UK

Sandburg A report July 2020 and Sandburg B Report June 2020

Please refer to the data sheet for the design of materials for construction