#### EU Declaration of Performance: ME-374



Marshalls Mono Ltd, Landscape House, Lowfields Business Park, Elland, West Yorkshire HX5 9HT

Registered in England: 509579

1. Unique identification code of the product-type:

#### Kerbs of Natural Stone

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

## **Tritanial Granite Kerb**

*3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:* 

# Domestic/Commercial Kerbstones for external uses (see Marshalls brochure for guidance on applications)

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

# Marshalls, Landscape House, Premier Way, Lowfields Business Park, Elland, West Yorkshire, HX5 9HT

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

## Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

#### System 4

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

#### BS EN 1343:2012

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

#### Not applicable

#### EU Declaration of Performance: ME-374



Marshalls Mono Ltd, Landscape House, Lowfields Business Park, Elland, West Yorkshire HX5 9HT

Registered in England: 509579

#### 9. Declared performance

Essential Characteristics	Performance	Relevant Clause of BS EN 1343:2012
Petrographic	Denomination: Grey to dark grey, fine grained, with microporphyritic texture, fresh BASALT, exhibiting occasional dark grey to black, irregular grains or grain aggregations. Stone hard to very hard and robust. Vietnam	4.1.1
Release of dangerous substances	NPD	4.11
Flexural Strength Lowest expected Value	11.34 MPa	4.4
Freeze/thaw resistance (general) Before and after 56 cycles	20/14.9MPa	4.3.1
Freeze/thaw resistance (De-Icing salts)	NPD	4.3.2
Polishing In Use	NPD	4.6.3

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

#### Not applicable

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Time Down .

Simon Bourne

#### **Group Operation Director**

Date: 9<sup>th</sup> July 2021

Place of Issue: Elland, Halifax, UK

All EU Declarations from January 2021 will show Version 1 so as to be complimentary with our GB Declaration of Performance.

Sandburg A report August 2011 and CLTT 3946 June 2021. CLTT 3915 B Report May 2021

Please refer to the data sheet for the design of materials for construction