Marshalls Mono Ltd, Landscape House, Lowfields Business Park, Elland, West Yorkshire HX5 9HT

Registered in England: 509579

1. Unique identification code of the product-type:

Slabs of Natural Stone

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Limestone Aluri Ochre Paving

3. Intended use or uses of the construction product, in accordance with the applicable designated technical specification, as foreseen by the manufacturer:

Domestic/Commercial Paving for external uses (see Marshalls brochure for guidance on applications)

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Marshalls, Landscape House, Premier Way, Lowfields Business Park, Elland, West Yorkshire, HX5 9HT

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 4

7. In case of the declaration of performance concerning a construction product covered by a designated standard:

BS EN 1341:2012

8. In case of the declaration of performance concerning a construction product for which a UK Assessment Document has been issued:

Not applicable

Marshalls Mono Ltd, Landscape House, Lowfields Business Park, Elland, West Yorkshire HX5 9HT

Registered in England: 509579

9. Declared performance

| Essential Characteristics | Performance | Relevant Clause of BS EN 1341:2012 |
|---|--|------------------------------------|
| Petrographic | Pale greyish beige to yellowish pale brown, mainly very fine to fine grained LIMESTONE | 4.1.1 |
| Release of dangerous substances | NPD | 4.11 |
| Flexural Strength Lowest expected Value | 12.52MPa | 4.4 |
| Slip Resistance (wet value) | 40 (mean value) | 4.6.1 |
| Skid Resistance | NPD (mean value) | 4.6.2 |
| Freeze/thaw resistance (general) Before and after 56 cycles | 23.36/27.8MPa | 4.3.1 |
| Freeze/thaw resistance (De-Icing salts) | NPD | 4.3.2 |
| Polishing In Use | NPD | 4.6.3 |

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

Not applicable

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, As it has effect in the United Kingdom" under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Simon Bourne

Chief Commercial Officer Place of Issue: Elland, Halifax, UK

Date: 8th April 2025

Test Group 5 Sandburg A 2022, CLTT 4861 2024