EU Declaration of Performance: ME-396



Marshalls Mono Ltd, Landscape House, Lowfields Business Park, Elland, West Yorkshire HX5 9HT

Registered in England: 509579

1. Unique identification code of the product-type:

Slabs of Natural Stone

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Granite Eclipse Paving Light

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Domestic/Commercial Paving for external uses (see Marshalls brochure for guidance on applications)

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Marshalls, Landscape House, Premier Way, Lowfields Business Park, Elland, West Yorkshire, HX5 9HT

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 4

7. In case of the declaration of conformity concerning a construction product covered by a harmonised standard:

BS EN 1341:2012

8. In case of the declaration of conformity concerning a construction product for which a European Technical Assessment has been issued:

Not applicable

EU Declaration of Performance: ME-396



Marshalls Mono Ltd, Landscape House, Lowfields Business Park, Elland, West Yorkshire HX5 9HT

Registered in England: 509579

9. Declared Performance

Essential Characteristics	Performance		Relevant Clause of BS EN 1341:2012
Petrographic	Off-white to pale grey with occasional black spots, mainly coarse grained, fresh GRANITE.		4.1.1
Release of dangerous substances	NPD		4.11
Flexural Strength Lowest expected Value	10.97MPa		4.4
Slip Resistance (wet value)	Polished	16	4.6.1
	Flamed	72	
	Fine picked	79	
Skid Resistance	NPD		4.6.2
	Riven or textured surface		
Freeze/thaw resistance			
(general)	10.5/11.5MPa		4.3.1
Before and after 56 cycles			
Freeze/thaw resistance	NPD		4.3.2
(De-Icing salts)			4.3.2
Polishing In Use	NPD		4.6.3

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

Not applicable

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Finn Down

Simon Bourne Chief Commercial Officer Date: 12th May 2025

Place of Issue: Elland, Halifax,

Test Group 180 Sandburg A March 2019, Sandburg B March 2019, CLTT 4613 2023