

This document is the Declaration of Performance for MLPFG-01 Marshalls Bought in Products – Clay Bricks and covers Point 9, Annex iii of the

## CONSTRUCTION PRODUCTS REGULATIONS

And gives details on the

## DECLARED PERFORMANCE

to the below harmonised standard

## Relevant Harmonised Standard BSEN 771-1:2011

**Products** Clay Masonry Units to Category II EN 771-1 **Size** HD, 215 x 102.5 x 65mm

**Uses** Units for external walling

Marshalls Mono Limited, Landscape House, Premier Way, Lowfields Business Park Elland, West Yorkshire, HX5 9HT

Year of first affixing CE Mark

13

DoP no.	MLPFG-01
Essential Characteristics	Performance Value
Dimensional Tolerances	Tolerance category T2; Range category R1
Compressive Strength To bed face	75N/mm²
Water Absorption	7%
Durability against Freeze/Thaw	F2
Active Soluble Salt Content	S2
Reaction to Fire	Class A1
Bond Strength Fixed value from EN 998-2	0.15N/mm²
Water Vapour Diffusion Coefficient EN 1745 tabulated value)	50/100
	Gross Density 1650kg/m <sup>3</sup>
Direct Airborne Sound Insulation	<b>Configuration</b> Vertically perforated 24-29% voids
Equivalent Thermal Conductivity	0.69 W/mK
Dimensional Stability/Moisture Movement	NPD
Dangerous Substances	See Note
Note: information on demonstrate substances will only be already when and subsequential in the	

Note: information on dangerous substances will only be given when and where required in the appropriate form. See Annex ZA3 of BS EN 771-1:2011

Products are offered in line with the requirements of Attestation Level 4 as designated under the Construction Products Regulations (2011) Annex V. I Hereby declare that the products named above are in conformity with the essential requirements of the Construction Products Regulations and the ZA Annex within the following Standard when installed in accordance with Marshalls' installation guidelines.

EN 771-1:2011

## **Declaration of Performance**

Signed: Full name: Tom Poole

Position: Managing Director Group

Operations Date: 30<sup>th</sup> October 2014