GB Declaration of Performance: **MMS-MORTAR -33**

Marshalls Mono Ltd, Landscape House, Lowfields Business Park, Elland, West Yorkshire HX5 9HT Registered in England: 509579

1. Unique identification code of the product-type:

Designed Mortar for Masonry

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Leeds – M12

3. Intended use or uses of the construction product, in accordance with the applicable designated technical specification, as foreseen by the manufacturer:

General Purpose masonry for external elements subject to use in structural applications.

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Marshalls Mortars and Screeds Leeds Plant, Quarry Lane, Woodkirk, Dewsbury, WF12 7JJ

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

Attestation Level 2+

Certificate Number 0086-CPR-740496

7. In case of the declaration of performance concerning a construction product covered by a designated standard:

BS EN 998-2:2016

8. In case of the declaration of performance concerning a construction product for which a UK Assessment Document has been issued:

Not applicable

Marshalls

Marshalls Mono Ltd, Landscape House, Lowfields Business Park, Elland, West Yorkshire HX5 9HT Registered in England: 509579

9. Declared performance

Essential Characteristics		Performance	Relevant Clause of BS EN 998-2
Compressive Strength		Minimum Strength of 12N/mm2	5.4.1 BSEN 998-2:2016
Bond Strength	**Sheer Bond**	0.15N/mm2	5.4.2 BSEN 998-2:2016
	Flexural Bond	NPD	5.4.2.2 BSEN 998-2:2016
Content of Chlorides		0.0.42%	5.2.2 BSEN 998-2:2016
Reaction to Fire		Class A1	5.6 BSEN 998-2:2016
Water Absorption		0.39kg (m2min0.5)	5.4.3 BSEN 998-2:2016
Water Vapour Permeability		µ 15/35	5.4.4 BSEN 998-2:2016
Thermal Conductivity		0.83 W/Mk (tab.Mean Value P=50%)	5.4.6 BSEN 998-2:2016
Durability		Satisfactory	5.4.7 BSEN 998-2:2016

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

Not applicable

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, As it has effect in the United Kingdom" under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Simon Bourne

Chief Executive Officer

Date: 6th April 2026

Place of Issue: Elland, Halifax, UK

Test data taken from Type Test CLTT 5220 10/3/26