

*1. Unique identification code of the product-type:*

**Kerbs of Natural Stone**

*2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):*

**Scoutmoor Sawn Kerb**

*3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:*

**Domestic/Commercial Kerbstones for external uses (see Marshall's brochure for guidance on applications)**

*4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):*

**Marshall's, Natural Stone, Cromwell Saws, Southowram, Halifax, West Yorkshire, HX3 9SZ.**

*5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):*

**Not applicable**

*6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:*

**System 4**

*7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:*

**BS EN 1343:2012**

*8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:*

**Not applicable**

*9. Declared performance*

| Essential Characteristics   | Performance   | Performance   | Relevant Clause of BS EN 1343:2012 |
|---|---|---|------------------------------------|
| <b>Petrographic</b>   | Denomination: Pale greenish grey fine-grained sandstone/Gritstone, from Appleton Quarry, Shepley, Huddersfield. | Denomination: Pale Grey and pale grey/blue to pale green/grey, mainly fine grained, cross bedded Sandstone from Whitworth Quarry, Whitworth, Greater Manchester | 4.1.1                              |
| <b>Release of dangerous substances</b>                                | NPD   | NPD   | 4.11                               |
| <b>Flexural Strength</b><br>Lowest expected Value                     | 17.49MPa  | 20.09MPa  | 4.4                                |
| <b>Freeze/thaw resistance (general)</b><br>Before and after 56 cycles | 14.79/14.6MPa   | 24.3/20.4MPa  | 4.3.1                              |
| <b>Freeze/thaw resistance (De-Icing salts)</b>                        | NPD   | NPD   | 4.3.2                              |
| <b>Polishing In Use</b>   | NPD   | NPD   | 4.6.3                              |

*Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:*

**Not applicable**

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



Simon Bourne

Date: 8<sup>th</sup> January 2025

Chief Commerical Officer.

Place of Issue: Elland, Halifax, UK

Please refer to the data sheet for the design of materials for construction.

Appleton A report Sandberg September 2022, B report CLTT 4820  
Whitworth A report Sandburg July 2017 report CLTT 4531 May 2023  
Scout Moor Quarry closed