

1. Unique identification code of the product-type:

Slabs of Natural Stone

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Scout Moor Natural Stone Paving

Capital, Flamed, fine Sawn, Diamond Wire Sawn

3. Intended use or uses of the construction product, in accordance with the applicable designated technical specification, as foreseen by the manufacturer:

Domestic/Commercial Paving for external uses (see Marshalls brochure for guidance on applications)

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Marshalls, Natural Stone, Cromwell Saws, Southowram, Halifax, West Yorkshire, HX3 9SZ.

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 4

7. In case of the declaration of performance concerning a construction product covered by a designated standard:

BS EN 1341:2012

8. In case of the declaration of performance concerning a construction product for which a UK Assessment Document has been issued:

Not applicable

GB Declaration of Performance: MNSP -14



Marshall's Mono Ltd, Landscape House, Lowfields Business Park, Elland, West Yorkshire HX5 9HT

Registered in England: 509579

9. Declared performance

Essential Characteristics	Performance	Performance	Relevant Clause of BS EN 1341:2012
Petrographic	Appleton Quarry West Yorkshire Denomination: Pale greenish grey fined sandstone/Gritstone, orange/brown, well compacted generally hard and strong.	Whitworth Quarry, Greater Manchester Denomination: Pale Grey and pale grey/blue to pale green/grey, mainly fine grained, cross bedded Sandstone	4.1.1
Release of dangerous substances	NPD	NPD	4.11
Flexural Strength Lowest expected Value	17.49MPa	20.98MPa	4.4
Slip Resistance (wet value)	Diamond Sawn 78	Diamond Sawn 86	4.6.1
	Capital NPD	Capital NPD	
	Flamed NPD	Flamed NPD	
Skid Resistance	NPD	NPD	4.6.2
Freeze/thaw resistance. Before and after 56 cycles	14.79/14.6MPa	24.28/20.4MPa	4.3.1
Freeze/thaw resistance. (De-icing salts)	NPD	NPD	4.3.2
Polishing In Use	NPD	NPD	4.6.3

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

Not applicable

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, As it has effect in the United Kingdom" under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Simon Bourne

Date: 8th January 2025

Chief Commerical Officer.

Place of Issue: Elland, Halifax, UK

Please refer to the data sheet for the design of materials for construction.

Whitworth A report Sandburg July 2017 B Report CLTT 4531 25/05/023

Appleton A report Sandburg September 2022 B Report CLTT 4820 05/04/2024

Please refer to the data sheet for the design of materials for construction.