GB Declaration of Performance MV -39



Marshalls Mono Ltd, Landscape House, Lowfields Business Park, Elland, West Yorkshire HX5 9HT

Registered in England: 509579

1. Unique identification code of the product-type:

Dry-pressed ceramic tiles, with water absorption Eb<0.5%

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Symphony Elements Corton

Bronze, Copper, Iron, Cobalt

3. Intended use or uses of the construction product, in accordance with the applicable designated technical specification, as foreseen by the manufacturer:

For internal and external walls and floorings

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Marshalls, Landscape House, Premier Way, Lowfields Business Park, Elland, West Yorkshire, HX5 9HT

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 4

7. In case of the declaration of conformity concerning a construction product covered by a designated standard:

BS EN 14411:2012

8. In case of the declaration of performance concerning a construction product for which a UK I Assessment Document has been issued:

Not applicable

GB Declaration of Performance MV -39



Marshalls Mono Ltd, Landscape House, Lowfields Business Park, Elland, West Yorkshire HX5 9HT

Registered in England: 509579

9. Declared performance

Essential Characteristics	Performance	Relevant Clause of BS EN 14411:2012
Reaction to Fire	Class A1 Without testing (see decision 96/603/EC, as amended	B.14
Release of dangerous substances	Cadmium NPD	C.3 a) EN 10545-15
	Lead NPD	C.3 b) EN 10545-15
Breaking Strength Thickness > 7,5 mm Thickness < 7,5 mm	>1.300 N >700 N	B-2) EN10545-4
Slipperiness	R11/C	89 CEN/TS 16165
Tactility	NPD	B.15 CEN/TS 15209
Bond Strength/Adhesion, only for wall tiles: Cementitious adhesives type C2	> 1N/mm2	B-10 a) EN12004:2007+a1:2012-4.1
Thermal shock resistance	Pass	B6 10545-9
	Internal Uses Pass	B.8 EN 10545-12
Durability;	External Uses (Freeze-Thaw Resistance Pass	B.8 EN 10545-12

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

Not applicable

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, As it has effect in the United Kingdom" under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Am berrow .

Simon Bourne Group Operations Director

Date: 22nd February 2021

Place of Issue: Elland, Halifax, UK