

*1. Unique identification code of the product-type:*

**Porcelain Tiles (Dry-pressed ceramic tiles, with water absorption  $E_b < 0.5\%$ )**

*2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):*

**VedaStone Porcelain Paving and Setts**

**Grey Multi, Buff Multi, Dark Grey Multi**

*3. Intended use or uses of the construction product, in accordance with the applicable designated technical specification, as foreseen by the manufacturer:*

**For internal and external walls and floorings**

*4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):*

**Marshalls, Landscape House, Premier Way, Lowfields Business Park, Elland, West Yorkshire, HX5 9HT**

*5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):*

**Not applicable**

*6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:*

**System 4**

*7. In case of the declaration of performance concerning a construction product covered by a designated standard:*

**BS EN 14411:2012**

*8. In case of the declaration of performance concerning a construction product for which a UK Assessment Document has been issued:*

**Not applicable**

*9. Declared performance*

| Essential Characteristics       | Performance   | Relevant Clause of BS EN 14411:2012 |
|---------------------------------|---|-------------------------------------|
| Reaction to Fire                | Class A1  | B.14<br>EN ISO 1182:2020            |
| Release of dangerous substances | Cadmium Not detected  | C.3 a)<br>EN 10545-15               |
|                                 | Lead Not detected   | C.3 b)<br>EN 10545-15               |
| Breaking Strength               | >5000N  | EN ISO: 10545-4                     |
| Slip Resistance                 | R11<br>PTV: 45-54   | CEN/TS<br>16165:2012<br>Annex C     |
| Tactility                       | NPD   | B.15<br>CEN/TS 15209                |
| Durability;                     | <b>Internal Uses</b><br>Pass  | B.8<br>EN 10545-12                  |
|                                 | <b>External Uses (Freeze/Thaw Resistance)</b><br>Pass (No visual defect after 100 cycles) | B.8<br>EN 10545-12                  |

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

**Not applicable**

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, As it has effect in the United Kingdom” under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Simon Bourne  
Chief Executive Officer

Date: 5<sup>th</sup> May 2026

Place of Issue: Elland, Halifax, UK