GB Declaration of Performance: MW-10



Marshalls Mono Ltd, Landscape House, Lowfields Business Park, Elland, West Yorkshire HX5 9HT

Registered in England: 509579

1. Unique identification code of the product-type:

Precast Concrete

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Buxton Walling

3. Intended use or uses of the construction product, in accordance with the applicable designated technical specification, as foreseen by the manufacturer:

Domestic and Commercial use in Walls, Columns and Partitions

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Marshalls, Brookfoot Works, Southowram, Halifax, West Yorkshire, HX3 9SY

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 2+

7. In case of the declaration of performance concerning a construction product covered by a designated standard:

BS EN 771-5:2011

8. In case of the declaration of performance concerning a construction product for which a UK Assessment Document has been issued:

Not applicable



GB Declaration of Performance: MW-10

Marshalls Mono Ltd, Landscape House, Lowfields Business Park, Elland, West Yorkshire HX5 9HT *9. Declared performance*

Registered in England: 509579

Essential Requirement	Performance Value	Relevant Clause within EN 771-5:2011
Dimensions and Dimensional Tolerances	D3 Length ±3mm Width & Height ±3mm	Clauses 5.2.1 & 5.2.2 BSEN 771- 5:2011
Configuration of units	Solid configuration without voids.	Clause 5.3.2 BSEN 771-5:2011
Mean Compressive Strength Homogeneous Category 1 Units. Full Mortar Bed without voids.	>50.96N/mm²	Clause 5.5.1 BSEN 771-5:2011
Dimensional Stability (Moisture Movement)	1.21mm/m	Clause 5.9 BSEN 771-5:2011
Bond Strength	Shear Bond Characteristic Tested 0.18N/mm² Flexural Bond Parallel Failure 0.32N/mm² Mortar Designation iii	Clause 5.12 BSEN 771-5:2011 Clause 5.13 BSEN 771-5:2011
Reaction to Fire	Class A1	Clause 5.11 BSEN 771-5:2011
Water Absorption by Capillarity	< 1.28 g/m ²	Clause 5.11 BSEN 771-5:2011
Water Vapour Permeability	Fine Face Walling 5/15μ Ash Walling 50/150μ	Clause 5.10 BSEN 771-5:2011
Direct Airborne Sound Insulation	Fine Face Walling 5/15μ	Clause 5.10 BSEN 771-5:2011
	Ash Walling 50/150μ	
	Density 2.253Kg/m³ Tolerance category D3	Clause 5.4 BSEN 771-5:2011
Thermal Resistance Tabulated values BS EN 772-13	Configuration	As above
Durability against Freeze Thaw	Dimension and tolerances	As Above

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

Not applicable

GB Declaration of Performance: MW-10



Marshalls Mono Ltd, Landscape House, Lowfields Business Park, Elland, West Yorkshire HX5 9HT

Registered in England: 509579

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, As it has effect in the United Kingdom" under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Simon Bourne

Chief Commercial Officer

Amm Down.

Version History: Updated due to change in Director's responsibilities.

Date: 23rd July 2024

Place of Issue: Elland, Halifax, UK