

*1. Unique identification code of the product-type:*

**Precast Concrete**

*2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):*

**Brookfoot Epoch Walling**

*3. Intended use or uses of the construction product, in accordance with the applicable designated technical specification, as foreseen by the manufacturer:*

**Domestic and Commercial use in Walls, Columns and Partitions**

*4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):*

**Marshalls, West Lane Works, Southowram, Halifax, West Yorkshire, HX3 9TW**

*5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):*

**Not applicable**

*6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:*

**System 2+**

*7. In case of the declaration of performance concerning a construction product covered by a designated standard:*

**BS EN 771-5:2011+A1**

*8. In case of the declaration of performance concerning a construction product for which a UKI Assessment Document has been issued:*

**0086-CPR-586567**

*9. Declared performance*

<b>Essential Requirement</b>	<b>Performance Value</b>	<b>Relevant Clause within EN 771-5:2011+A1</b>
<b>Dimensions and Dimensional Tolerances</b>	D3 Length $\pm 3\text{mm}$ Width & Height $\pm 3\text{mm}$	Clauses 5.2.1 & 5.2.2 BSEN 771-5:2011
<b>Configuration of units</b>	Solid configuration without voids.	Clause 5.3.2 BSEN 771-5:2011
<b>Mean Compressive Strength Homogeneous Category 1 Units. Full Mortar Bed without voids.</b>	$>20\text{N/mm}^2$	Clause 5.5.1 BSEN 771-5:2011
<b>Dimensional Stability (Moisture Movement)</b>	$\leq 0.6\text{mm/m}$	Clause 5.9 BSEN 771-5:2011
<b>Bond Strength</b>	Shear Bond Strength $0,15\text{ N/mm}^2$ (tabulated value)	Clause 5.12 BSEN 771-5:2011
	Flexural Bond Strength NPD	Clause 5.13 BSEN 771-5:2011
<b>Reaction to Fire</b>	Class A1	Clause 5.11 BSEN 771-5:2011
<b>Water Absorption by Capillarity</b>	$< 9\text{g/m}^2\text{s} \cdot 0.5$	Clause 5.11 BSEN 771-5:2011
<b>Water Vapour Permeability</b>	$5/15\mu$ (Tabulated value)	Clause 5.10 BSEN 771-5:2011
<b>Direct Airborne Sound Insulation</b>	Density $2300\text{kg/m}^2$	Clause 5.4 BSEN 771-5:2011
<b>Thermal Resistance Tabulated values BS EN 772-13</b>	$1.16\text{W/mk}$	Clause 5.6 BSEN 771-5:2011
<b>Durability against Freeze Thaw</b>	Frost Resistant	Clause 5.7 BSEN 771-5:2011

*Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:*

**Not applicable**

## GB Declaration of Performance: MW-11



Marshalls Mono Ltd, Landscape House, Lowfields Business Park, Elland, West Yorkshire HX5 9HT

Registered in England: 509579

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, As it has effect in the United Kingdom” under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

A handwritten signature in black ink, appearing to read "Simon Bourne", with a stylized flourish at the end.

Simon Bourne

Chief Executive Officer

Date: 24<sup>th</sup> April 2026

Place of Issue: Elland, Halifax, UK