

*1. Unique identification code of the product-type:*

**Precast Concrete**

*2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):*

**Cromwell Walling**

**Split Face, Rustic**

*3. Intended use or uses of the construction product, in accordance with the applicable designated technical specification, as foreseen by the manufacturer:*

**Domestic and Commercial use in Walls, Columns and Partitions**

*4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):*

**Marshall's, Brookfoot Works, Southowram, Halifax, West Yorkshire, HX3 9SY**

*5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):*

**Not applicable**

*6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:*

**System 2+**

*7. In case of the declaration of performance concerning a construction product covered by a designated standard:*

**BS EN 771-5:2011+A1**

*8. In case of the declaration of performance concerning a construction product for which a UKI Assessment Document has been issued:*

**0086-CPR-586567**

*9. Declared performance*

Essential Requirement	Performance Value	Relevant Clause within EN 771-5:2011+A1
<b>Dimensions and Dimensional Tolerances</b>	D3 Length $\pm 3\text{mm}$ Width & Height $\pm 3\text{mm}$	Clauses 5.2.1 & 5.2.2 BSEN 771-5:2011
<b>Configuration of units</b>	Solid configuration without voids.	Clause 5.3.2 BSEN 771-5:2011
<b>Mean Compressive Strength Homogeneous Category 1 Units. Full Mortar Bed without voids.</b>	$>50.96\text{N/mm}^2$	Clause 5.5.1 BSEN 771-5:2011
<b>Dimensional Stability (Moisture Movement)</b>	0.52 mm/m	Clause 5.9 BSEN 771-5:2011
<b>Bond Strength</b>	Shear Bond Characteristic Tested $0.211\text{N/mm}^2$	Clause 5.12 BSEN 771-5:2011
	Flexural Bond Parallel Failure $0.17\text{N/mm}^2$ Mortar Designation iii	Clause 5.13 BSEN 771-5:2011
<b>Reaction to Fire</b>	Class A1	Clause 5.11 BSEN 771-5:2011
<b>Water Absorption by Capillarity</b>	$1.28\text{ g/m}^2$	Clause 5.11 BSEN 771-5:2011
<b>Water Vapour Permeability</b>	Fine Face Walling 5/10 $\mu$	Clause 5.10 BSEN 771-5:2011
	Ash Walling 50/150 $\mu$	
<b>Direct Airborne Sound Insulation</b>	Density $2340\text{Kg/m}^3$	Clause 5.4 BSEN 771-5:2011
	Tolerance category D3	
	Configuration	As above
	Dimension and tolerances	As Above
<b>Thermal Resistance Tabulated values BS EN 772-13</b>	$1.16\text{W/mk}$	Clause 5.6 BSEN 771-5:2011
<b>Durability against Freeze Thaw</b>	F2 to EN772-22	Clause 5.7 BSEN 771-5:2011

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

**Not applicable**

## GB Declaration of Performance: MW-12



Marshalls Mono Ltd, Landscape House, Lowfields Business Park, Elland, West Yorkshire HX5 9HT

Registered in England: 509579

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, As it has effect in the United Kingdom" under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

A handwritten signature in black ink, appearing to read "Simon Bourne", with a stylized flourish at the end.

Simon Bourne

Chief Commercial Officer

Date: 28<sup>th</sup> February 2025

Place of Issue: Elland, Halifax, UK

Version History: Updated due to change in Director's responsibilities.