

1. Unique identification code of the product-type:

Manufactured stone masonry Cat 11

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Argent Walling

3. Intended use or uses of the construction product, in accordance with the applicable designated technical specification, as foreseen by the manufacturer:

In masonry walls, columns and partitions

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Marshall's, Sandy Works, Sunderland Road, Sandy, Bedfordshire, SG19 1QY

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

Level 4

7. In case of the declaration of performance concerning a construction product covered by a designated standard:

BS EN 771-5:2011+A1:2015

8. In case of the declaration of performance concerning a construction product for which a UK Assessment Document has been issued:

Not applicable

GB Declaration of Performance: MW-17



Marshall's Mono Ltd, Landscape House, Lowfields Business Park, Elland, West Yorkshire HX5 9HT

Registered in England: 509579

9. Declared performance

Essential Characteristics	Performance	Relevant Clause of BS EN 771-5:2011+A1:2015
Dimensions and dimensional tolerances	D1	5.2.1 Dimensions 5.2.2 Dimensional tolerances
Configuration	Solid with a natural stone face and in a grey colour	5.3.2
Compressive Strength	69.55 N/mm ² *	5.5
Dimensional Stability (Moisture movement)	0.61mm/m	5.9
Bond Strength	Shear Bond Strength 0.22 N/mm ²	5.12
	Flexural Bond Strength 0.18 N/mm ² Mortar designation (iii)	
Reaction to Fire	Class A1	5.11
Water Absorption by Capillarity	2.5 g/m ² *	5.8.1
Water Vapour Permeability	5/15	5.10
Direct Airbourne Sound Insulation	2.130kg/m ³	5.4
Thermal Resistance	1.34W/mK	5.6
Durability against freeze-thaw	F2	5.7
Dangerous substances	NPD	5.14

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

Not applicable

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, As it has effect in the United Kingdom” under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Simon Bourne

Chief Commercial Officer

Date: 1st November 2024

Place of Issue: Elland, Halifax, UK

Version History: Updated due to change in Director's responsibilities and change from Level 2+ to Level 4