

*1. Unique identification code of the product-type:*

**Aggregates**

*2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):*

**Stainton 10-20mm**

*3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:*

**Preparation of concrete for use in Buildings, roads and other civil engineering works.**

*4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):*

**Stainton Quarry, Ruddell Mill Lane, Stainton, Maltby, South Yorkshire, S66 7RH**

*5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):*

**Not applicable**

*6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:*

**System 4**

*7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:*

**BS EN 13242:2002**

*8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:*

**Not applicable**

## EU Declaration of Performance: S-04



Marshall's Mono Ltd, Landscape House, Lowfields Business Park, Elland, West Yorkshire HX5 9HT

Registered in England: 509579

### 9. Declared performance –

Essential Characteristics	Performance	Relevant Clause of BS EN 13242:2002
Particle Grading	10/20mm	4.4
Particle Shape	Angular to Sub-angular	4.2
Particle Density	1.29 Mg/m <sup>3</sup> loose/1.44 Mg/m <sup>3</sup> Compacted	5.4
Fines Content	NPD	4.6
Fines Quality	NPD	4.7
Percentage of crushed & broken surfaces	100%	4.5
Resistance to fragmentation/crushing (LA)	34*	5.2
Volume Stability	NPD	6.5.2
Water Absorption	5.3%	5.5
Composition/content		
Petrographic Description	Dolomite	6.2
Acid Soluble Sulphates	NPD	6.3
Total Sulphur	NPD	6.5.1
Constituents which alter the rate of setting and hardening concrete	NPD	
Resistance to attrition	16	5.3
Dangerous Substances	NPD	
Durability against weathering	NPD	7.2
Durability against Freeze/thaw	1.0%	7.3.2

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

### Not applicable

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Simon Bourne

Chief Commercial Officer

Celtest report reference 116692

Date: 22<sup>nd</sup> October 2024

Place of Issue: Elland, Halifax, UK